



## NO24FDW-A

The rear compatibility of opticalCON MTP® 24 chassis fitting with standard MTP® 24 (ELITE male with 20 N springforce) breakout cable allows easy adaptation to fiber standard connectors such as LC, SC, ST. The approved dust shutter ensures high mating cycles and minimal maintenance.

## Features & Benefits

- ✓ Ruggedized and dirt-protected 24-channel fiber optic connection system
- ✓ For point-to-point multichannel routing
- ✓ Laser protective metal shutter seals dust proof with two-component rubber gasket
- ✓ IP65 ingress protection in mated condition with SCDP-\*
- ✓ Accommodates standard MTP® ELITE MALE with 20 N springforce connectors on the rear for simple installation

## Technical Information

Product	
Title	NO24FDW-A
Gender	female

## Mechanical

Insertion force	< 45 N
Withdrawal force	< 45 N
Lifetime (typ.)	2'500 mating cycles
Locking force	1'000 N
Wiresize	
Locking device	Push-Pull
Mounting direction	Front mounting
Chassis shape	D

## Environmental

Temperature range	-40 °C to +75 °C
Protection class	IP65 in mated condition in combination with SCDP-*

## Optical

Insertion loss	< 0.9 dB / connection
----------------	-----------------------